

Experimental Question 2: An Optical "Black Box"

MARKING SCHEME

| a) 0.4 | Writing the reflection law | 0.1 | |
|---------------|--|-----|--|
| | Correct result | 0.3 | |
| b) 0.5 | Correct answer | 0.5 | |
| c) 0.8 | Value of φ | 0.6 | Partial credit for φ corresponding to the edge of the reflection pattern – 0.2 |
| | Error estimation | 0.2 | 0.02°-0.1° – Full credit of 0.2 0.11°-0.5° – Partial credit of 0.1 |
| d) 0.5 | Correct answer | 0.5 | |
| e) 1.4 | Measuring the distance <i>y</i> between the sample and the bench | 0.1 | |
| | Choosing a large enough distance y | 0.3 | At least 70cm – 0.3 25cm-69cm – 0.1 |
| | Distance <i>x</i> between two positions of the stake (or equivalent) | 0.1 | |
| | Calculating δ_0 from measurements | 0.1 | |
| | Value of δ_0 | 0.7 | 30.6°-31.6° - 0.7 |
| | | | 30.3°-32.0° - 0.5 |
| | | | 30.0°-32.3° - 0.3 |
| | | | 29.6°-32.7° - 0.1 |
| | Error estimation | 0.1 | |
| f) 1.4 | Measuring the distance <i>y</i> between the sample and the bench | 0.1 | |
| | Choosing a large enough distance y | 0.3 | At least 70cm – 0.3 25cm-69cm – 0.1 |
| | Distance <i>x</i> between two positions of the stake (or equivalent) | 0.1 | |
| | Calculating δ_{min} from measurements | 0.1 | |
| | Value of δ_{min} | 0.7 | 30.4°-31.0° - 0.7 |
| | | | 30.1°-31.3° - 0.5 |
| | | | 29.8°-31.6° - 0.3 |
| | | | 29.5°-32.0° - 0.1 |
| | Error estimation | 0.1 | |
| g) 0.8 | Writing equations for <i>n</i> | 0.2 | |
| | Extracting an expression for <i>n</i> | 0.4 | |
| | Using the correct angle of the prism | 0.2 | |
| h) 0.7 | Value of n_v | 0.3 | 1.601-1.607 - 0.3 |
| | | | 1.595-1.613 - 0.2 |
| | | | 1.574-1.634 - 0.1 |

Experimental Competition 5 May 2011



| | Error calculation | 0.3 | |
|---------------|---|------|--|
| | Value of the error | 0.1 | |
| i) 1.0 | Measured distance <i>y</i> to the screen | 0.1 | |
| | Large enough range of points <i>x</i> on the screen | 0.3 | At least 20cm – 0.3 |
| | | | 15cm-19cm - 0.2 |
| | | | 10cm-14cm - 0.1 |
| | Enough fringes | 0.2 | At least 8 fringes – 0.2 |
| | | | 6-7 fringes – 0.1 |
| | Correct counting | 0.2 | |
| | Converting distances to angles | 0.2 | |
| | Penalty for no errors in measurements | -0.1 | |
| | Penalty for no errors in θ | -0.1 | |
| j) 1.5 | Graph | 0.5 | Correct axes (e.g. $\sin \theta$ vs. <i>m</i>), properly marked – |
| | | | 0.1 |
| | | | Reasonably linear -0.3 |
| | | | Efficient use of the graph paper's area -0.1 |
| | Finding the slope | 0.1 | |
| | Error of the slope | 0.1 | |
| | Result for <i>d</i> | 0.6 | 49.3μm-50.7μm - 0.6 |
| | | | 48.5μm-51.5μm - 0.4 |
| | | | 47μm-53μm - 0.2 |
| | Calculation of error in <i>d</i> | 0.1 | |
| | Value of error in d | 0.1 | |
| k) 1.0 | Measuring the deflection angle | 0.3 | Measuring the distance <i>x</i> along the screen or |
| | | | counting fringes – 0.1 |
| | | | Deducing the angle -0.2 |
| | Value of n_r | 0.5 | 1.577-1.581 - 0.5 |
| | | | 1.573-1.585 - 0.3 |
| | | | 1.567-1.590 - 0.2 |
| | | | 1.550-1.610 - 0.1 |
| | Calculation of error in n_r | 0.1 | |
| | Value of error in n_r | 0.1 | |