



## Grading Scheme for Experimental Problem – 2

No fraction less than 0.1 marks should be given for any answer. Nowhere marks are to be deducted according to the marking scheme.

### Part 1

| Quantity observed               | Magnitude to be checked                          | criteria   | marks | Total |
|---------------------------------|--|--|-------|-------|
| <b>Part 1</b>                   |  |  |       |       |
| <b>a)Coil 1 air core</b>        |  |  |       |       |
| Measured voltages               | $ V - V_{R'} $ ( $R' \approx 450 \Omega$ )       | $\leq 0.15 \text{ V}$                            | 0.1   |       |
| Measured voltages               | $V_{A'}, V, V_{R'}, V_o$                         | Measured once                                    | 0.1   |       |
|                                 | $V_{A'}, V, V_{R'}, V_o$                         | Measured second time reversing the DMM polarity  | 0.1   |       |
| Calculated value of $Z_1$       |  | Between 435-465 $\Omega$                         | 0.1   |       |
| Calculated value of $R_1$       |  | Between 40-47 $\Omega$                           | 0.1   |       |
| Calculated value of $L_1$       |  | Between 0.069 - 0.073 H                          | 0.1   |       |
| Standard uncertainty $u_s(R_1)$ |  | Between 1.1 and 1.2                              | 0.1   |       |
| Expanded uncertainty in $R_1$   |  | $\pm 3 \Omega$                                   | 0.1   |       |
| Expanded uncertainty in $L_1$   |  | $\pm 0.0002 \text{ H}$                           | 0.1   |       |
|                                 |  |  |       | 0.9   |
| <b>b)Coil 2 air core</b>        |  |  |       |       |
| Measured voltages               | $ V - V_{R'} $ ( $R' \approx 350 - 360 \Omega$ ) | $\leq 0.15 \text{ V}$                            | 0.1   |       |
|                                 | $V_{A'}, V, V_{R'}, V_o$                         | Measured once                                    | 0.1   |       |
|                                 | $V_{A'}, V, V_{R'}, V_o$                         | Measured second time reversing the DMM polarity  | 0.1   |       |
| Calculated value of $Z_2$       |  | Between 335-365 $\Omega$                         | 0.1   |       |
| Calculated value of $R_2$       |  | Between 40 – 47 $\Omega$                         | 0.1   |       |
| Calculated value of $L_2$       |  | Between 0.052 - 0.059 H                          | 0.1   |       |
| Standard uncertainty $u_s(R_2)$ |  | Between 0.85 and 0.97                            | 0.1   |       |
| Expanded uncertainty in $R_2$   |  | $\pm 3 \Omega$                                   | 0.1   |       |
| Expanded uncertainty in $L_2$   |  | $\pm 0.0001 \text{ H}$ or $\pm 0.0002 \text{ H}$ | 0.1   |       |
|                                 |  |  |       | 0.9   |
| <b>c) Coil 1 Al core</b>        |  |  |       |       |
| Measured voltages               | $ V - V_{R'} $ ( $R' \approx 300 \Omega$ )       | $\leq 0.15 \text{ V}$                            | 0.1   |       |



|                                   |                          |   |     |     |
|-----------------------------------|--------------------------|---|-----|-----|
|                                   | $V_{A'}, V, V_{R'}, V_o$ | Measured once                                   |     |     |
|                                   | $V_{A'}, V, V_{R'}, V_o$ | Measured second time reversing the DMM polarity | 0.1 |     |
| Calculated value of $Z_1^*$       |                          | Between 280-310 $\Omega$                        | 0.1 |     |
| Calculated value of $R_1^*$       |                          | Between 100 – 110 $\Omega$                      | 0.1 |     |
| Calculated value of $L_1^*$       |                          | Between 0.042 - 0.046 H                         | 0.1 |     |
| Standard uncertainty $u_s(R_1^*)$ |                          | Between 1.1 and 1.4                             | 0.1 |     |
| Expanded uncertainty in $R_1^*$   |                          | $\pm 3 \Omega$                                  | 0.1 |     |
| Expanded uncertainty in $L_1^*$   |                          | $\pm 0.0002$ H                                  | 0.1 |     |
|                                   |                          |   |     | 0.8 |

|                                   |  |   |     |     |
|-----------------------------------|--|---|-----|-----|
| <b>d) Coil 2 Al core</b>          |  |   |     |     |
| Measured voltages                 | $ V - V_{R'} $ ( $R' \approx 280 \Omega$ ) | $\leq 0.15$ V                                   | 0.1 |     |
|                                   | $V_{A'}, V, V_{R'}, V_o$                   | Measured once                                   |     |     |
|                                   | $V_{A'}, V, V_{R'}, V_o$                   | Measured second time reversing the DMM polarity | 0.1 |     |
| Calculated value of $Z_2^*$       |  | Between 275 – 285 $\Omega$                      | 0.1 |     |
| Calculated value of $R_2^*$       |  | Between 64-76 $\Omega$                          | 0.1 |     |
| Calculated value of $L_2^*$       |  | Between 0.040 - 0.044 H                         | 0.1 |     |
| Standard uncertainty $u_s(R_2^*)$ |  | Between 0.91 and 1.2                            | 0.1 |     |
| Expanded uncertainty in $R_2^*$   |  | $\pm 2 \Omega$ or $\pm 3 \Omega$                | 0.1 |     |
| Expanded uncertainty in $L_2^*$   |  | $\pm 0.0002$ H                                  | 0.1 |     |
|                                   |  |   |     | 0.8 |

|                                       |  |                                   |     |     |
|---------------------------------------|--|-----------------------------------|-----|-----|
| <b>Part 2</b>                         |  |                                   |     |     |
| <b>f) M &amp; k</b>                   |  |                                   |     |     |
| Calculated value of $M_{air}$         | $\omega M = R' (V_o / V_{R'})$<br>mean of both coils   | 0.052 H ( range of $\pm 0.002$ H) | 0.1 |     |
| $k_{air}$                             |  | 0.84 (range of $\pm 0.02$ )       | 0.1 |     |
| Calculated value of $M_{Al}$ or $M^*$ | $\omega M^* = R' (V_o / V_{R'})$<br>mean of both coils | 0.034 H ( range of $\pm 0.001$ H) | 0.1 |     |
| $k_{Al}$ or $k^*$                     | Observed $k^* = k - 0.04$                              | (allow $\pm 0.02$ )               | 0.1 |     |
|                                       |  |                                   |     | 0.4 |
| <b>g) Measured voltages</b>           | $R_L$ and $V_{A'}, V, V_{R'}, V_o$                     |                                   |     |     |
|                                       | no of readings :                                       | 5                                 | 0.4 |     |
|                                       | no of readings :                                       | 6                                 | add | 0.1 |



|  |   |   |     |     |
|--|---|---|-----|-----|
|  | no of readings :  | 7 <b>add</b>  | 0.1 |     |
|  | Choice of $R_L$ and choice of step;<br>Effect of $R_L$ will be noticed when its<br>magnitude is of the order of $X_S$ . | with equal steps 100,200,300<br>$\Omega$ etc to cover range up to<br>700 to 1000 $\Omega$ | 0.1 |     |
|  | Two readings for each voltage   | with reversal for correction of<br>asymmetry  | 0.1 |     |
|  |   |   |     | 0.8 |
| <b>h)</b> Linearised relation                          | $(\omega M)^2(I_p/I_s)^2 = (R_s + R_L)^2 + X_S^2$<br>Or $(R_s + R_L)^2 = (\omega M)^2(I_p/I_s)^2 - X_S^2$               | Correct rearrangement   | 0.2 |     |
|  |   |   |     | 0.2 |
| <b>i)</b>  | Number of secondary data generated<br>from data of (g)  | 4   | 0.2 |     |
|  |   | 5 <b>add</b>  | 0.2 |     |
|  |   | 6 <b>add</b>  | 0.2 |     |
| Calculated values                                      | $I_p = V_R / 300$   | Correct calculation   | 0.1 |     |
| Calculated values                                      | $I_s = V_o / R_L$   | Correct calculation   | 0.1 |     |
| Calculated values                                      | $(R_s + R_L)^2$   | Choice of correct value of $R_s$<br>(= $R_2$ of coil 2: air core)                         | 0.1 |     |
|  |   |   |     | 0.9 |
| <b>j)</b> Graph of $(R_s + R_L)^2$<br>vs $(I_p/I_s)^2$ | Proper choice of scale to occupy<br>graph space (about 70% or more)   |   | 0.1 |     |
|  | Proper choice of origin<br>To get intercept   |   | 0.1 |     |
|  | M from slope  | Between 0.050-0.54 H  | 0.1 |     |
|  |   | If between 0.051-0.52 H <b>add</b>  | 0.1 |     |
|  | $X_s$ from intercept  | Between 320-385 $\Omega$  | 0.1 |     |
|  |   | If between 335-360 $\Omega$ <b>add</b>  | 0.1 |     |
|  | More than 5 points on straight line   |   | 0.1 |     |
|  |   |   |     | 0.7 |
| <b>Part 3</b>  |   |   |     |     |
| <b>k)</b> Calculations of<br>$R_{PE}$ and $X_{PE}$     |   |   |     |     |
|  | $R_{PE} = (300/2)[(V_A^2 - V_P^2) / V_R^2 - 1]$   | Correct formula used  | 0.1 |     |
|  | Number of data points calculated  | 5   | 0.1 |     |
|  | Number of data points calculated  | 6 <b>add</b>  | 0.1 |     |
|  |   |   |     |     |
|  | $X_{PE} = [Z_{PE}^2 - R_{PE}^2]^{1/2}$  | Correct formula used  | 0.1 |     |
|  | Number of data points calculated  | 5   | 0.1 |     |
|  | Number of data points calculated  | 6 <b>add</b>  | 0.1 |     |



|   |   |   |     |     |
|---|---|---|-----|-----|
|   |   |   |     | 0.6 |
| <b>l) Calculations of <math>R_R</math> and <math>X_R</math></b> |   |   |     |     |
|   | $R_R = (R_s + R_L)/(I_p/I_s)^2$                       | Correct formula used                                      | 0.1 |     |
|   | Number of data points calculated                      | 5   | 0.1 |     |
|   | Number of data points calculated                      | 6 <b>add</b>  | 0.1 |     |
|   |   |   |     |     |
|   | $X_R = X_s/(I_p/I_s)^2$                               | Correct formula used                                      | 0.1 |     |
|   | Number of data points calculated                      | 5   | 0.1 |     |
|   | Number of data points calculated                      | 6 <b>add</b>  | 0.1 |     |
|   |   |   |     | 0.6 |
|   |   |   |     |     |
| <b>m) Graph of <math>X_{pE}</math> vs <math>X_R</math></b>      |   |   |     |     |
|   | Right choice of scale (to occupy more than 70% space) |   | 0.1 |     |
|   | Right choice of origin to get intercept               |   | 0.1 |     |
|   | slope   | Between -0.9 & -1.1                                       | 0.1 |     |
|   | Intercept   | $X_p$ (found from part 1) $\pm 20 \Omega$                 | 0.1 |     |
|   | More than 5 points on the st.line                     |   | 0.1 |     |
|   | Inference $X_p - X_R = X_{pE}$                        |   | 0.1 |     |
|   |   |   |     | 0.6 |
| <b>n) Graph of <math>R_R</math> vs <math>R_L</math></b>         |   |   |     |     |
|   | Choice of scale (to occupy more than 70% space)       |   | 0.1 |     |
|   | Smooth curve  |   | 0.1 |     |
|   | Peak shown is unambiguous                             |   | 0.1 |     |
|   | $R_R$ is maximum at $R_L = X_s - R_s$                 | $R_L$ should be $X_2 - R_2$ in a range of $\pm 20 \Omega$ | 0.1 |     |
|   |   | If the range is $\pm 5$ <b>add</b>                        | 0.2 |     |
|   |   |   |     | 0.6 |

|   |  |  |     |     |
|---|--|--|-----|-----|
| <b>Part 4</b>                             |  |  |     |     |
| <b>o) Model for AI core</b>               |  |  |     |     |
|   | $L_{core}/R_{core} = (X_p - X^*)/(R^* - R_p)2\pi f$                  | Correct formula showing clear understanding of concepts                              | 0.4 |     |
|   | Calculated value for coil 1  | $L_c/R_c \approx 0.0046 \text{ H}/\Omega$ (a range of $\pm 0.003 \text{ H}/\Omega$ ) | 0.2 |     |
|   | Calculated value for coil 2  | $L_c/R_c \approx 0.0046 \text{ H}/\Omega$ (range of $\pm 0.003 \text{ H}/\Omega$ )   | 0.2 |     |
|   |  |  |     | 0.8 |
| <b>p) Power loss in core measurements</b> |  |  |     |     |
|   | $V_A, V, V_{R'}, V_o$ with $R' = 300 \Omega$ and $R_L = 1000 \Omega$ |  |     |     |



|  |   |   |     |      |
|--|---|---|-----|------|
|  | same  | With reversal of polarity                           | 0.1 |      |
|  | $\Delta P = I_p^2(R_{PE} - R_p) - I_s^2(R_S + R_L)$ | Correct concept                                     | 0.2 |      |
|  | Calculated value                                    | $\Delta P = 0.016 \text{ W } (\pm 0.001 \text{ W})$ | 0.1 |      |
|  |   |   |     | 0.4  |
|  |   |   |     |      |
|  |   |   |     | 10.0 |

Note on uncertainty in R1, L1 etc.:

The combined standard uncertainty  $u_c = \sqrt{u_{sy}^2 + u_{res}^2}$ . Expanded uncertainty U is rounded up value of  $2u_c$ .

In the case of R, worst case systematic error is given by

$$\Delta R = R'[(V_A \Delta V_A - V \Delta V) / V_{R'}^2 - (V_A^2 - V^2) \Delta V_{R'} / V_{R'}^3] \text{ and } u_{sy}(R) = \Delta R / \sqrt{3}.$$

The standard uncertainty due to resolution in measurement is accepted as equal to 0.3 of the least count. On 20 V range the least count is 0.01 V. So the standard uncertainty is 0.003 V. The standard uncertainty in R due to resolution is given by

$$u_{res}(R) = R'[(V_A \times 0.003)^2 + (V \times 0.003)^2 / V_{R'}^2 + \{(V_A^2 - V^2) \times 0.003 / V_{R'}^3\}]^{1/2}.$$

$$Z^2 = R^2 + X^2. \text{ Therefore, } u(X) = [(Zu(Z))^2 + (Ru(R))^2]^{1/2}; u(Z) = \sqrt{u_{sy}^2(Z) + u_{res}^2(Z)}.$$